PRODUCT DATA SHEET

UNICRIMP QT200S

Qcrimp Natural Cable Ties 200mm x 4.8mm

Manufacturer: Scolmore Group

GTIN: 5055287039569

Family: Cable Ties

Range: Standard Range



DESCRIPTION

A cable tie is a band or length of strap, manufactured from a class of polymeric materials known as polyamides (Nylon 6/6). The width, length, and head area employ ratcheting mechanisms, which allow for locking as necessary for "bundling" items / cables together. Nylon possesses an outstanding balance of properties, combined strength, moderate stiffness, high service temperature, and a high level of toughness. Nylon cable ties are particularly resistant to repeated impact; they have a low coefficient of friction, and excellent abrasion resistance. Nylon is resistance to fuels, lubricants, and most chemicals, but is attacked by phenols, strong acids, and oxidizing agents. General-purpose nylon is suitable for use in most practical applications at continuous temperatures up to 85°C. Nylon 6/6, the grade most often used for cable tie production, meets UL 94V-2 flammability ratings. Its working temperature range is from -40°C to 85°C.

- Made from polyamide (Nylon 6/6)
- Self-locking for fast and easy application
- Resistant to repeated impact
- Working temperature range of -40°C to 85°C

TECHNICAL SPECIFICATION

ETIM Class: Cable tie (EC000046)

Primary Features

Band width (mm)	4.8	Length belt/tape/tie (mm)	200
Colour	Colourless	Material	Plastic

Additional Features

Band closure	Plastic lip/-cam	Mounting temperature (°C)	-40 - 85
Fluorescent	No	Operating temperature (°C)	-40 - 85
Halogen free	No	Surface protection	Untreated
Inflammability class of insulation material acc. with UL94	V2	Transparent	No
MIL approval	No	Type of fastening	None
Min. tensile strength (N)	220	UL approval	No
Model	External toothing	VG approval	No

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 19-04-2024

Trade Tariff Commodity Code: Not supplied

Country of Origin: Not supplied

Scolmore Group, Scolmore House, Mariner, Tamworth, B79 7UL
01827 63454 sales@scolmore.com http://www.scolmore.com

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 21/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.