

PRODUCT DATA SHEET

Ansell Lighting APRIP/1/MP1



Prism Pro CCT Fire Rated Downlight Dual Wattage Multi Pack - 10 Pack

Manufacturer: Ansell Lighting

GTIN: 5056144272563

Family: [Display]

Range: Prism Pro Fire Rated



DESCRIPTION

IP65 dimmable LED Fire Rated Downlight suitable for residential and hospitality applications. CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable. Innovative 2 part detachable connector and remote driver. Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations

- IP65 dimmable LED Fire Rated Downlight suitable for residential and hospitality applications
- CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering a choice of 2 outputs, in one luminaire
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Remote driver with 2x1.5mm + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Low profile design and remote driver allows installation into shallow ceiling voids
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations
- Wide 65° beam angle for increased light distribution

TECHNICAL SPECIFICATION

ETIM Class: Downlight / spot luminaire / floodlight (EC001744)



Primary Features

Colour of light	White	Maximum system power (W)	7
Colour temperature (K)	2700 - 6000	Nominal voltage (V)	220 - 240
Housing colour	White	Number of lamps	1
Light source included	Yes		

Additional Features

Adjustability	Not adjustable	Suitable for ceiling mounting	Yes
Beam angle	Wide beam 40-80°	Suitable for recessed mounting	Yes
Colour consistency (McAdam ellipse)	SDCM6	Suitable for surface mounting	No
Colour rendering index (CRI/Ra)	80-89	Suitable for suspended mounting	No
Height/depth (mm)	58	Suitable for wall mounting	No
Length (mm)	62	Unified Glare Rating (UGR)	25
Outer diameter (mm)	90	With light sensor	No
Protection class according to IEC 61140	I	With movement sensor	No

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 15-07-2025

Trade Tariff Commodity Code: 9405119090

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 17/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.