PRODUCT DATA SHEET

Ansell Lighting APRIPXM/1

Prism Pro XM Fire Rated Downlight

Manufacturer: Ansell Lighting

GTIN: 5056687329731

Family: Not supplied

Range: Prism Pro XM

DESCRIPTION

Prism Pro XM Fire Rated Downlight APRIPXM/1 IP65. Material: Polycarbonate,Steel. Finish: White. Wattage: 5W/7W W. Lumens: 640lm - 820lm (4000K) lm. Colour temperature: 2700K/3000K/4000K/6000K K. CRI: 80. Operating temperature: -10°C - 35°C. Dimmable.

- IP65 dimmable LED Fire Rated Downlight suitable for residential and hospitality applications
- TM66 2.5 assessed – independently evaluated against the industry standard for measuring the circularity of lighting products.
- CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Patent-applied modular design with replaceable light engine and driver — extend product life and reduce waste through easy part replacement.
- Fast-fit plug with lever terminals provide easy connection
- Low profile design allows installation into shallow ceiling voids
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations
- Wide 60° beam angle for increased light distribution

TECHNICAL SPECIFICATION

ETIM Class: Downlight / spot luminaire / floodlight (EC001744)

Primary Features

Degree of protection (IP), front side	IP65	Nominal current (mA)	0.03 - 0.03
Housing colour	White	Number of lamps	1
Light source type	LED non-replaceable		

Additional Features

Beam angle	Wide beam 40-80°	Height/depth (mm)	63
Beam angle adjustable	No	Length (mm)	0
Colour consistency (McAdam ellipse)	SDCM5	Outer diameter (mm)	88
Colour rendering index (CRI/Ra)	80-89	Unified Glare Rating (UGR)	28
Dimmable	Yes	Width (mm)	0
Dimming DALI	No		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 24-02-2026

Trade Tariff Commodity Code: 9405119090

Country of Origin: Not supplied

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD
01942 433 333 saleswarrington@anselluk.com http://www.anselluk.com

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 20/03/2026.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.