

PRODUCT DATA SHEET

Termination Technology HS6.4BLK


Term Tech Heatshrink 2:1 Ratio 6.4mmØ Expanded, 3.2mmØ Recovered Black (Per Metre)

Manufacturer: Termination Technology

GTIN: 5060964214757

Family: Sleeving & Heatshrink

Range: Heatshrink Sleeving (2:1 Ratio)



DESCRIPTION

The Termination Technology range of thin wall Cross linked Polyolefin Heatshrink is designed for commercial use with common uses including insulation, wire bundling, colour coding and mechanical protection. Available in a range of colours and sizes, all cut to metre as required. Specialist Heatshrink end caps, breakout boots, joints and adhesive lined versions also available from stock.

- Manufactured from black crosslinked polyolefin
- 2:1 Shrink ratio to half the original diameter
- 6.4mmØ Expanded, 3.2mmØ recovered
- 0.56mm Recovered wall thickness
- -55°C to +135°C Temperature rating
- +90°C to start shrinking
- Approved to UL 224 VW-1; MIL-I-23053/5 Class 1 & 3
- Minimum 19.7kV/mm dielectric strength, tested to ASTM D-2671
- Min 10^{13} Ohm-cm volume resistivity, tested to ASTM D-876
- HSG110V and HSG240 heat guns both available and suitable for Heatshrink

TECHNICAL SPECIFICATION

ETIM Class: Assortment box with heat-shrink tubing segments (EC001049)



Features

Shrink rate	2:1	With tool	No
With inner glue	No		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 19-04-2024

Trade Tariff Commodity Code: Not supplied

Country of Origin: Not supplied

Termination Technology, Unit 4B, 4C, 4D & 1A, Croft End Industrial Estate, Croft End Road, St. George, Bristol, BS5 7UW

☎ 01179 354900

✉ sales@termtech.co.uk

🌐 <http://www.termtech.co.uk>

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 21/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.