

PRODUCT DATA SHEET

Termination Technology RMP48

Term Tech Pre-Insulated Terminals Red Male Push On 0.5mm²-1.5mm² Cable 4.8mm Width (Bag of 100)

Manufacturer: Termination Technology

GTIN: 5060659808971

Family: Crimp Terminals

Range: Pre Insulated Terminals Red 0.5mm²-1.5mm²



DESCRIPTION

The Termination Technology range of pre-insulated terminals are colour coded to cover 0.5mm² up to 6mm² cable sizes and includes a wide variety of types from rings, forks, pins, blades and more. Manufactured from oxygen-free high conductivity copper which is electro-tin plated for excellent resistance to corrosion. PVC insulation with a maximum working temperature of 75°C. All supplied in display counter packs of 100.

- Red PVC insulation
- Electro-tin plated copper terminal
- Suitable for cables with 0.5-1.5mm² cable cross section
- Male spade terminal with a 4.8mm spade width
- Suitable for use with our RFP48 and RFIP48 female push-on terminals

TECHNICAL SPECIFICATION

ETIM Class: Disconnect terminals (EC000516)

Features

Colour insulation	Red	Plug dimensions	Flat 4.8x0.5 mm
Halogen free	No	Surface protection	Tinned
Insulation	Partially isolated	With cam clamp	No
Material	Copper	With tap spreader	No
Material insulation	Polyvinyl chloride (PVC)		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 19-04-2024

Trade Tariff Commodity Code: Not supplied

Country of Origin: Not supplied

Termination Technology, Unit 4B, 4C, 4D & 1A, Croft End Industrial Estate, Croft End Road, St. George, Bristol, BS5 7UW

☎ 01179 354900

✉ sales@termtech.co.uk

🌐 <http://www.termtech.co.uk>

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 21/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.