

PRODUCT DATA SHEET

Ansell Lighting AGAM/1



Gamma CCT Multi Wattage White

Manufacturer: Ansell Lighting

GTIN: 5056687317141

Family: [Amenity]

Range: Gamma



DESCRIPTION

Ultra slim modern polycarbonate wall/ceiling light with high efficiency up to 120lm/W. CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire.

- Ultra slim modern polycarbonate wall/ceiling light suitable for education, residential and ancillary applications
- High efficiency up to 120lm/W
- CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Centralised loop-in, loop-out terminals with push button release feature ensures a quick and easy installation
- Innovative hinged hatch compartment allows quick access to adjust microwave and emergency option settings
- Additional profile channeling runs parallel to cable glands, allowing easy installation for applications where the cable runs across the ceiling
- Satin Chrome and Black trim bezel accessories available
- /MWS and /MWS/M3 versions operate as "Primary" and can be used in conjunction with standard "Secondary"
- /MWS and MWS/M3 has integral photocell isolation switch
- Non-dimmable

TECHNICAL SPECIFICATION

ETIM Class: Ceiling / wall luminaire (EC002892)



Primary Features

Colour of light	White	Light source type	LED replaceable
Housing colour	White	Maximum system power (W)	13
Light source included	Yes	Voltage type	AC

Additional Features

Beam angle	Wide beam 40-80°	Impact resistance (IK rating)	IK08
Beam angle adjustable	No	Light diffuser type	Diffuser
Bluetooth operated	No	Light distribution	Symmetric
Colour consistency (McAdam ellipse)	SDCM3	Light outlet	Direct
Colour rendering index (CRI/Ra)	80-89	Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	80
Colour temperature switchable	Discrete positions	Lumen setting adjustable	No
Compatible with Amazon Alexa	No	Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Compatible with Apple HomeKit	No	Power factor	9
Compatible with Google Assistant	No	Protection class according to IEC 61140	II
Constant luminous flux control	No	Rated life time L70/B50 at 25 °C (h)	50000
Control gear included	Yes	Replaceable control gear	Yes
Cover material	Plastic opal	Suitable for ceiling mounting	Yes
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	50	Suitable for surface mounting	Yes
Fit for workplace acc. EN 12464-1	No	Suitable for suspended mounting	No
Height/depth (mm)	58	Type of cabling	Suitable for through wiring
Housing material	Plastic	Unified Glare Rating (UGR)	24
Housing surface protection	Untreated	Width (mm)	294
IFTTT support available	No		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 15-07-2025

Trade Tariff Commodity Code: 9405114090

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

**Disclaimer**

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 17/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.