

PRODUCT DATA SHEET

Ansell Lighting AEDELED50/CW

Eden Floodlight 50W Cool White

Manufacturer: Ansell Lighting

GTIN: 5056144245536

Family: [Floodlighting]

Range: Eden



DESCRIPTION

Compact economic polycarbonate LED floodlight, textured polycarbonate finish and polished faceted reflector. Bracket design allows installation without LED removal and is pre-wired with 1m of rubber insulated cable. PIR versions with manual override. Ideal for semi-commercial and gardens.

- Compact and economic aluminium LED floodlight suitable for semi commercial applications
- Bracket design allows installation without removing mounting bracket
- PIR versions complete with manual override facility (10W-50W only)
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- Polycarbonate spike accessory allowing installation into lawn and garden applications (10W-30W only)
- Non-dimmable

TECHNICAL SPECIFICATION

ETIM Class: Downlight / spot luminaire / floodlight (EC001744)



Primary Features

Colour of light	White	Maximum system power (W)	50
Colour temperature (K)	4000 - 4000	Nominal voltage (V)	220 - 240
Light source included	Yes		

Additional Features

Adjustability	Swivelling	Suitable for light-track mounting	No
Colour consistency (McAdam ellipse)	SDCM6	Suitable for recessed mounting	No
Colour rendering index (CRI/Ra)	80-89	Suitable for surface mounting	Yes
Control gear included	Yes	Suitable for suspended mounting	No
Height/depth (mm)	175	Suitable for traverse mounting	No
Housing material	Aluminium	Suitable for wall mounting	Yes
Impact resistance (IK rating)	IK06	Width (mm)	35
Length (mm)	197	With light sensor	No
Protection class according to IEC 61140	I	With movement sensor	No
Suitable for ceiling mounting	No		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 15-07-2025

Trade Tariff Commodity Code: 9405423990

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 17/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.