PRODUCT DATA SHEET

WYLEX NHTPSF63

63A 3P+N Fuse Combination Unit c/w Fuses

Manufacturer: Electrium Sales Ltd

GTIN: 5013601025575

Family: Commercial Circuit Protection

Range: NH Fuse combination Units

DESCRIPTION

NH Fuse combination switches range from 20A to 800A in single pole and 3 pole configurations and comply to BS EN 60947. A robust steel enclosure with ingress protection to IP4X. The units have a utilisation category of AC23A, and fused short circuit capacity of 80kA.

- Supplied with 63A BS88 fuses
- /IP4X rated steel enclosure 420mmH x 263mmW x 188mmD. Front door reversible, opening to 180°
- Operating handle can be padlocked.
- Accommodates cable spreading room up to 70mm² 4 core. Spreading room is allowed for at one end only. To fit a 4 core cable at both ends an additional cable spreader (NHCSB2) is required
- RAL7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 60947-3

TECHNICAL SPECIFICATION

ETIM Class: Fuse switch disconnector (EC001040)

Primary Features

Number of poles	3

Additional Features

Conditioned rated short-circuit current Iq (kA)	50	Rated short-time withstand current Icw (kA)	1.5
Degree of protection (IP), front side	IP40	Suitable for busbar mounting	No
Equipped with connectors	Yes	Suitable for fuses	Shape A2/A3
Max. rated operation voltage Ue AC (V)	415	Type of control element	Door coupling rotary drive
Motor drive integrated	No	Type of electrical connection of main circuit	Cable clamp
Motor drive optional	No	Version as emergency stop installation	No
Position control element	Front	Version as main switch	Yes
Rated operation power at AC-23, 400 V (kW)	18.5	Version as safety switch	No
Rated permanent current Iu (A)	63	With error protection	No

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 19-04-2024

Trade Tariff Commodity Code: Not supplied

Country of Origin: Not supplied

Electrium Sales Ltd, Commercial Centre, Lakeside Plaza, Walkmill Lane, Bridgtown, Cannock, WS11 0XE
01543 455 000 info@electrium.co.uk http://www.electrium.co.uk

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 18/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.